



通道功能 channel function

1	調光 Dimmer	
2	Strobe 閃頻	
3	顏色盤 Color	
4	色盤調控 Color wheel macro	
5	X 軸 Pan	
6	Y 軸 Tilt	
7	變焦 ZOOM	
8	對焦 focus	
9	光圈大小 Iris	
10	固定圖案盤 STATIC GOBO/WHEEL	
11	旋轉圖案 GOBO Auto	
12	圖案旋轉 GOBO Rotate	
13	X 軸微動 Pan Fine	
14	Y 軸微動 Tilt Fine	
15	稜鏡 Prism	
16	稜鏡自轉 Prism Rotation	
17	C 三基色	
18	M 三基色	
19	Y 三基色	
20	Color filter 彩色濾光鏡	
21	CMY效果 Effect	
22	CMY Speed CMY 速度	
23	XY Speed XY 轉速度	
24	回復 Reset	

TECHNICAL PARAMETER

Power: AC110V-240V 50-60Hz  
 Lamp: MSI 1200W  
 Power: 1600W  
 Control: DMX 512  
 Channels: 24CH  
 Size: 630×585×890mm  
 N.W: 52kg  
 G.W: 59kg

PERFORMANCE TRAIT

8 main colors adding 8 mixed colors, achieving high speed single way rainbow and scrolling effect  
 Mechanical linear DIMMER and 1---10 times/s high speed strobe effect  
 Horizontal 540° and vertical 252° scanning range, smooth scanning action and accurate orientation  
 Precise adjustment on horizontal and vertical position  
 Precise speed adjustment on horizontal and vertical position  
 Stopper function on the rotating effect wheel and position moving  
 5 rotating elegant GOBO (3 stainless rotating GOBO+1 glass+1 white)  
 Pattern internal light rotating function, freely adjusting fast, low speed, clockwise and anticlockwise  
 GOBO position adjustment  
 Automatic focusing function  
 Double manifold, color temperature effect  
 Fog manufacturing Prism, comet lens, repeated pattern prism effect, prism automatic rotating effect  
 3 primary color effect(C,M,Y)  
 3 primary speed adjustment  
 Built-in over heat protection and high voltage protection  
 Compatible with DMX 512 international digital single  
 According to various kind of safety standards, IP 20 protect grades, the cable accords to the CE20/22 standard

